

DESCRIPTION

Traditional antistatic paper paste, strippable, for mechanized or manual application.



USE

- Interior decorative plaster for walls and ceilings on all common substrates, with textured, crushed, or brushed effects.
- Can be waxed.

TECHNICAL SPECIFICATIONS

TYPICAL SPREADABILITY:

2 to 3 kg/m² per coat depending on the substrate's surface regularity.

DENSITY:

1,7 +/- 0,1 kg/l

SOLID CONTENT:

- Solid content by weight: 54%
- Solid content by volume: 22%

APPLICATION CONDITIONS:

- +8°C to +35°C
- Maximum humidity 70% RH

PH:

8 ± 1

CLEANING TOOLS:

With water

RECOMMENDED THICKNESSES:

DRYING:

- 12 to 36 hours on average depending on application thickness, temperature, ventilation, humidity, and substrate type. Sanding and covering: after complete drying.

PACKAGING AND STORAGE

- 25 kg plastic bucket.

- Shelf life of 1 year in unopened original packaging, protected from frost and excessive heat.

METHOD OF APPLICATION

SUBSTRATES:

- Sur fonds pulvérulents, appliquer un fixateur.
- Plaster, plaster tiles, plaster boards, cement render, old backgrounds, old paints, printed wood.

ENVIRONMENTAL INFORMATION

- VOC content: < 1 g/L.
- Indoor Air Emission Class



CHARACTERISTICS

- Fire classification: A2-s1, d0 according to European standard EN 13501-1.
- Classification: family III class 2 according to AFNOR NF T 36-005, compliant with AFNOR standard NF T 30-608.

PREPARATION OF SUBSTRATE:

- The supports, preparatory work, and conditions of application will be in accordance with the DTU and current standards.

APPLICATION TIPS:

- Mix before use if necessary.
- Spatula knife, Italian trowel.
- Applicable to the projection machine, nozzles of 4-6 or 8mm.

RECOMMENDATIONS:

- Ventilate the room during application and drying.
- Use clean and properly maintained PPE: gloves and eye protection designed against liquid splashes, mask during sanding operations.
- To clean tools, scrape off excess and immerse in a minimum amount of water.
- Do not dispose of residues in the sewer. Dispose of contents/container at a hazardous or special waste collection center.
- Conserver à l'abri du gel et de la chaleur.
- Tightly reseal the container after use.
- Ensure adequate ventilation to remove excess humidity and speed up drying.

HEALTH AND SAFETY

The safety data sheet is available on the website: <https://icp-alltek.com/en-gb/documentation/>