

DESCRIPTION

Ecrú-colored plaster made from natural mineral fillers, organic binder, and additives.

USE

- Interior plaster for walls and ceilings on all common substrates.
- Ready-mix rough-coat and smoothing plaster to correct surface irregularities before applying a finishing plaster.
- Direct application on aerated concrete and raw concrete.



TECHNICAL SPECIFICATIONS

TYPICAL SPREADABILITY:

3 to 6 kg/m² per coat depending on the substrate's surface regularity.

DENSITY:

1,7 +/- 0,1 kg/l

SOLID CONTENT:

- Solid content by weight: 77%
- Solid content by volume: 61%

APPLICATION CONDITIONS:

- +8°C to +35°C
- Maximum humidity 70% RH

PH:

8 ± 1

CLEANING TOOLS:

With water

RECOMMENDED THICKNESSES:

- Minimum thickness: 1 mm
- Maximum thickness: 4 mm

DRYING:

- 5 days in the case of bonded installation.
- 48 hours in the case of installation on metal framing.

PACKAGING AND STORAGE

- 25 kg plastic bag with handle.

- Shelf life of 1 year in unopened original packaging, protected from frost and excessive heat.

ENVIRONMENTAL INFORMATION

- VOC content: < 1 g/L.
- Indoor Air Emission Class

CHARACTERISTICS

- Fire classification: A2-s1, d0 according to European standard EN 13501-1.
- Classification: family III class 2 according to AFNOR standard NF T 36-005, compliant with AFNOR standard NF T 30-608.

HEALTH AND SAFETY

The safety data sheet is available on the website: <https://icp-alltek.com/en-gb/documentation/>

METHOD OF APPLICATION

SUBSTRATES:

- Concrete, cellular concrete and all common supports, old or new.

PREPARATION OF SUBSTRATE:

- The supports, preparatory work, and conditions of application will be in accordance with the DTU and current standards.

APPLICATION TIPS:

- Mix before use if necessary.
- Spraying machine for nozzles from 4 to 6 mm
- Sanding with P80 to P100 grit.

RECOMMENDATIONS:

- Ventilate the room during application and drying.
- Use clean and properly maintained PPE: gloves and eye protection designed against liquid splashes, mask during sanding operations.
- To clean tools, scrape off excess and immerse in a minimum amount of water.
- Do not dispose of residues in the sewer. Dispose of contents/container at a hazardous or special waste collection center.
- Store protected from frost and heat.

- Ensure adequate ventilation to remove excess humidity and speed up drying.