

DESCRIPTION

Coltek is a transparent invisible adhesive for applying masking paper before spraying.



USE

- Coltek is ready to use.
- Applied with a brush or airless spray to protect common building substrates (joinery, baseboards, concrete slabs, etc.) before plaster or paint application.

TECHNICAL SPECIFICATIONS

TYPICAL SPREADABILITY:

100 to 200 g/m².

DENSITY:

1,0 +/- 0,1 kg/l

APPLICATION CONDITIONS:

- +8°C to +35°C
- Maximum humidity 70% RH

PH:

8 ± 1

CLEANING TOOLS:

With water

DRYING:

- 12 to 24 hours on average.

PACKAGING AND STORAGE

- 25 kg plastic bucket.

- Shelf life of 1 year in unopened original packaging, protected from frost and excessive heat.

METHOD OF APPLICATION

PREPARATION OF SUBSTRATE:

- The supports, preparatory work, and conditions of application will be in accordance with the DTU and current standards.

APPLICATION TIPS:

- Applicable à la brosse.
- Applicable to airless.
- Apply a layer of COLTEK on the surface, then stick the non-adhesive masking paper. Use a thin paper (about 60g).
- After applying coatings or paints, quickly remove the soaked masking paper.

ENVIRONMENTAL INFORMATION

- VOC content: < 1 g/L.
- Indoor Air Emission Class



RECOMMENDATIONS:

- Ventilate the room during application and drying.
- Use clean and properly maintained PPE: gloves and eye protection designed against liquid splashes, mask during sanding operations.
- To clean tools, scrape off excess and immerse in a minimum amount of water.
- Do not dispose of residues in the sewer. Dispose of contents/container at a hazardous or special waste collection center.
- Conserver à l'abri du gel et de la chaleur.
- Tightly reseal the container after use.
- Ensure adequate ventilation to remove excess humidity and speed up drying.

HEALTH AND SAFETY

The safety data sheet is available on the website: <https://icp-alltek.com/en-gb/documentation/>