

## DESCRIPTION

Cryltek Mat is a semi-thick matte acrylic primer paint. It is used as an opacifying adhesion undercoat.



## USE

- Ideal as a primer/undercoat on plasterboard or on traditional substrates of bare buildings or those coated with well-adhered old paints.

## TECHNICAL SPECIFICATIONS

### TYPICAL SPREADABILITY:

7 to 8 m<sup>2</sup> per liter depending on the substrate type.

### DENSITY:

1,65 kg/l

### SOLID CONTENT:

- Solid content by weight: 67%
- Solid content by volume: 45%

### APPLICATION CONDITIONS:

- +8°C to +35°C
- Maximum humidity 70% RH

### PH:

8 ± 1

### CLEANING TOOLS:

With water

### DRYING:

- Dust-free in 30 minutes.
- Touch dry in 1 hour.

## PACKAGING AND STORAGE

- 25 kg plastic bucket.

- Shelf life of 1 year in unopened original packaging, protected from frost and excessive heat.

## METHOD OF APPLICATION

### SUBSTRATES:

- Cardboard plasterboards.
- Concrete, cement coating, cement fiber, old acrylic paints.
- Pre-printed coating.

## ENVIRONMENTAL INFORMATION

- EU limit value for this product (cat. A/a): 30 g/L (2010). This product contains a maximum of 2 g/L VOC.



## CHARACTERISTICS

- Classification: family I, class 7b2 according to AFNOR NF T 36-005.

### PREPARATION OF SUBSTRATE:

- The supports, preparatory work, and conditions of application will be in accordance with the DTU and current standards.

### APPLICATION TIPS:

- Airless machine: airless buses of 517. Apply in crossed passes.
- Brush, roller.
- 2% dilution if necessary.
- Dilution 10% for printing on plasterboards.

### RECOMMENDATIONS:

- Ventilate the room during application and drying.
- Use clean and properly maintained PPE: gloves and eye protection designed against liquid splashes, mask during sanding operations.
- To clean tools, scrape off excess and immerse in a minimum amount of water.
- Do not dispose of residues in the sewer. Dispose of contents/container at a hazardous or special waste collection center.
- Conserver à l'abri du gel et de la chaleur.
- Tightly reseal the container after use.
- Ensure adequate ventilation to remove excess humidity and speed up drying.

## HEALTH AND SAFETY

The safety data sheet is available on the website: <https://icp-alltek.com/en-gb/documentation/>