

DESCRIPTION

Ready-mix lacquer plaster. Particularly suitable for achieving an ultra-smooth surface for lacquer application. Easy to apply, very creamy texture, and excellent adhesion.



USE

- Interior plaster for walls and ceilings on all common smooth substrates.
- Enables type A paint finishes.
- Sealing of wooden joinery and repair work on plaster decorations, furniture lacquering.
- Suitable for filling shallow cracks.

TECHNICAL SPECIFICATIONS

TYPICAL SPREADABILITY:

1 litre/m² per mm thickness.

DENSITY:

1,7 +/-0,1 kg/l

SOLID CONTENT:

- Solid content by weight: 74%
- Solid content by volume: 56%

APPLICATION CONDITIONS:

- +8°C to +35°C
- Maximum humidity 70% RH

PH:

8 ± 1

CLEANING TOOLS:

With water

RECOMMENDED THICKNESSES:

- Minimum thickness: 0.1 mm
- Maximum thickness: 1 mm

DRYING:

- 2 to 12 hours on average depending on application thickness, temperature, ventilation, humidity, and substrate type.
- Sanding and covering: after complete drying.

PACKAGING AND STORAGE

- 400 ml plastic tube (ref. 101204).
- 3-liter plastic bucket (ref. 102440).

- Shelf life of 1 year in unopened original packaging, protected from frost and excessive heat.

METHOD OF APPLICATION

SUBSTRATES:

- Plaster, plaster tiles, plaster boards, cement render, old backgrounds, old paints, printed wood.
- On powdery substrates, apply a fixative.

ENVIRONMENTAL INFORMATION

- VOC content: < 1 g/L.
- Indoor Air Emission Class



CHARACTERISTICS

- Fire classification: A2-s1, d0 according to European standard EN 13501-1.
- Classification: family III class 2 according to AFNOR standard NF T 36-005.
- Product compliant with standard NF EN 16566.

PREPARATION OF SUBSTRATE:

- The supports, preparatory work, and conditions of application will be in accordance with the DTU and current standards.

APPLICATION TIPS:

- Spatula.
- Trowel with rounded edges.
- Sanding with grit P220 to P400.

RECOMMENDATIONS:

- Ventilate the room during application and drying.
- Use clean and properly maintained PPE: gloves and eye protection designed against liquid splashes, mask during sanding operations.
- To clean tools, scrape off excess and immerse in a minimum amount of water.
- Do not dispose of residues in the sewer. Dispose of contents/container at a hazardous or special waste collection center.
- Conserver à l'abri du gel et de la chaleur.
- Tightly reseal the container after use.
- Ensure adequate ventilation to remove excess humidity and speed up drying.

HEALTH AND SAFETY

The safety data sheet is available on the website: <https://icp-alltek.com/en-gb/documentation/>