

DESCRIPTION

Tight primer-plaster without smoothing for a neat preparation of plasterboards. Masks joint tape marks and gives walls and ceilings a higher-level finish. White color with a velvety matte appearance.

USE

- Interior primer plaster for walls and ceilings on plasterboard, exclusively for airless application.
- Self-leveling without smoothing at application, and can be covered with all types of paints.



TECHNICAL SPECIFICATIONS

TYPICAL SPREADABILITY:

0.5 to 0.6 kg/m² per coat depending on the substrate's surface regularity.

DENSITY:

1,6 +/- 0,1 kg/l

SOLID CONTENT:

- Solid content by weight: 66%
- Solid content by volume: 44%

APPLICATION CONDITIONS:

- +8°C to +35°C
- Maximum humidity 70% RH

PH:

8 ± 1

CLEANING TOOLS:

With water

RECOMMENDED THICKNESSES:

- Minimum thickness: 0.3 mm
- Maximum thickness: 0,4 mm

DRYING:

- Approximately 3 hours depending on application thickness, temperature, ventilation, humidity, and substrate type.

PACKAGING AND STORAGE

- 24 kg plastic bucket.

- Shelf life of 9 months in unopened original packaging, protected from frost and excessive heat.

METHOD OF APPLICATION

SUBSTRATES:

- Cardboard plasterboards.
- In finish on filling plaster.

ENVIRONMENTAL INFORMATION

- VOC content: < 8 g/L.
- Indoor Air Emission Class



CHARACTERISTICS

- Fire classification: A2-s1, d0 according to European standard EN 13501-1.
- Classification: family III class 2 according to AFNOR NF T 36-005, compliant with AFNOR standard NF T 30-608.

PREPARATION OF SUBSTRATE:

- The supports, preparatory work, and conditions of application will be in accordance with the DTU and current standards.

APPLICATION TIPS:

- The surfaces must be perfectly revised and sanded.
- Mix before use if necessary.
- All airless pumps, flow > 5 L (do not use a filter) for a perfect finish.
- Airless buses from 23 to 27 depending on the equipment used (follow the manufacturer's guidelines).

RECOMMENDATIONS:

- Ventilate the room during application and drying.
- Use clean and properly maintained PPE: gloves and eye protection designed against liquid splashes, mask during sanding operations.
- To clean tools, scrape off excess and immerse in a minimum amount of water.
- Do not dispose of residues in the sewer. Dispose of contents/container at a hazardous or special waste collection center.
- Conserver à l'abri du gel et de la chaleur.
- Tightly reseal the container after use.
- Ensure adequate ventilation to remove excess humidity and speed up drying.

HEALTH AND SAFETY

The safety data sheet is available on the website: <https://icp-alltek.com/en-gb/documentation/>