

DESCRIPTION

Alltek Spray Satin is a satin acrylic paint for all types of wall decoration work.



USE

- Ideal for finishing on glass fiber wall coverings, for new work and maintenance.

TECHNICAL SPECIFICATIONS

TYPICAL SPREADABILITY:

9 to 11 m² per liter depending on substrate and application method.

DENSITY:

1,3 +/- 0,1 kg/l

SOLID CONTENT:

- Solid content by weight: 61%
- Solid content by volume: 49%

APPLICATION CONDITIONS:

- +8°C to +35°C
- Maximum humidity 70% RH

PH:

8 ± 1

CLEANING TOOLS:

With water

DRYING:

- Dry in 30 minutes.
- Can be covered in 8 hours.

PACKAGING AND STORAGE

- Stackable 112 L returnable plastic drum with thermoformed protective cover.
- Shelf life of 1 year in unopened original packaging, protected from frost and excessive heat.

METHOD OF APPLICATION

SUBSTRATES:

- Concrete, coatings, cements.
- Bricks and terracotta tiles, plaster, plaster tiles, cardboard plasterboards.
- Wood and derivatives, old adhering painted surfaces in good condition.

ENVIRONMENTAL INFORMATION

- EU limit value for this product (cat. A/a): 30 g/L (2010). This product contains a maximum of 30 g/L VOC.



CHARACTERISTICS

- Classification: family I, class 7b2 according to AFNOR NF T 36-005.

PREPARATION OF SUBSTRATE:

- The supports, preparatory work, and conditions of application will be in accordance with the DTU and current standards.

APPLICATION TIPS:

- Airless machine: airless buses from 517 to 521.
- Applies in cross passes.

RECOMMENDATIONS:

- Ventilate the room during application and drying.
- Use clean and properly maintained PPE: gloves and eye protection designed against liquid splashes, mask during sanding operations.
- To clean tools, scrape off excess and immerse in a minimum amount of water.
- Do not dispose of residues in the sewer. Dispose of contents/container at a hazardous or special waste collection center.
- Store protected from frost and heat.
- Tightly reseal the container after use.
- Ensure adequate ventilation to remove excess humidity and speed up drying.

HEALTH AND SAFETY

The safety data sheet is available on the website: <https://icp-alltek.com/en-gb/documentation/>