# alltek®

Vos enduits de référence
**depuis 1951**

# Alltek Stucco Wax

Finishing wax | Manual application | Indoor application

## DESCRIPTION

Shiny transparent protective wax emulsion based on aqueous dispersion of wax and resin.

## USE

• Wax ideal for enhancing shine, deepening colors, and improving moisture resistance of decorative plasters such as Alltek Nuance Toscane.

## TECHNICAL SPECIFICATIONS

**TYPICAL SPREADABILITY:**

400 ml for approximately 10 m².

**DENSITY:**

0,8 +/- 0,1 kg/l

**SOLID CONTENT:**

• Solid content by weight: 50%

**APPLICATION CONDITIONS:**

• +8°C to +35°C
• Maximum humidity 70% RH

**PH:**

8 ± 1

**CLEANING TOOLS:**

With water

## PACKAGING AND STORAGE

• 400 ml jar.

• Shelf life of 1 year in unopened original packaging, protected from frost and excessive heat.

## ENVIRONMENTAL INFORMATION

• VOC content: < 1 g/L.
• Indoor Air Emission Class

## CHARACTERISTICS

• Transparent wax.
• Improves the wet abrasion resistance of the coated plaster.
• Increases gloss.

## METHOD OF APPLICATION

**SUBSTRATES:**

• Decorative finishes such as Alltek Nuance Toscane.
• Dry plasters.

**PREPARATION OF SUBSTRATE:**

• The supports, preparatory work, and conditions of application will be in accordance with the DTU and current standards.

**APPLICATION TIPS:**

• Apply in a crosswise manner while maintaining strong pressure: only a small amount of product is required.
• To achieve an optimal result, it is recommended to go over the surface several times and to brush while applying strong pressure.

**RECOMMENDATIONS:**

• Ventilate the room during application and drying.
• Use clean and properly maintained PPE: gloves and eye protection designed against liquid splashes, mask during sanding operations.
• To clean tools, scrape off excess and immerse in a minimum amount of water.
• Do not dispose of residues in the sewer. Dispose of contents/container at a hazardous or special waste collection center.
• Conserver à l'abri du gel et de la chaleur.
• Tightly reseal the container after use.
• Ensure adequate ventilation to remove excess humidity and speed up drying.

## HEALTH AND SAFETY

The safety data sheet is available on the website: https://icp-alltek.com/en-gb/documentation/