

DESCRIPTION

Adhesive technical membrane for joinery connections with our Alltek Spray Etanch'R plaster. It consists of a copolymer film combined with a non-woven fabric, featuring a double-sided adhesive strip on one edge and a polyester mesh on the other.



USE

- Using the 'AlltekTape + Etanch'R' membrane prevents any contact of the plaster with joinery where adhesion might be weaker.

TECHNICAL SPECIFICATIONS

APPLICATION CONDITIONS:

- +8°C to +35°C
- Maximum humidity 70% RH

PH:

8 ± 1

CLEANING TOOLS:

With water

PACKAGING AND STORAGE

- Carton of 3 rolls of 50 m for the 60 mm width.
- Shelf life of 1 year.

METHOD OF APPLICATION

SUBSTRATES:

- Smooth surfaces of woodwork.

PREPARATION OF SUBSTRATE:

- The supports, preparatory work, and conditions of application will be in accordance with the DTU and current standards.

APPLICATION TIPS:

- Attach the adhesive part along the profile of the support.
- Ménager des plis d'environ 2 cm dans chaque angle.
- Soak the open grid in the coating.

CHARACTERISTICS

- Dimensions: 60 mm x 50 m or 90 mm x 50 m

HEALTH AND SAFETY

The safety data sheet is available on the website: <https://icp-alltek.com/en-gb/documentation/>

RECOMMENDATIONS:

- Ventilate the room during application and drying.
- Use clean and properly maintained PPE: gloves and eye protection designed against liquid splashes, mask during sanding operations.
- To clean tools, scrape off excess and immerse in a minimum amount of water.
- Do not dispose of residues in the sewer. Dispose of contents/container at a hazardous or special waste collection center.
- Store protected from frost and heat.
- Ensure adequate ventilation to remove excess humidity and speed up drying.