

DESCRIPTION

Adhesive fiberglass mesh tape for wall-to-ceiling joints.



TECHNICAL SPECIFICATIONS

APPLICATION CONDITIONS:

- +8°C to +35°C
- Maximum humidity 70% RH

PH:

8 ± 1

CLEANING TOOLS:

With water

DRYING:

- Approximately 24 hours depending on application thickness, temperature, ventilation, humidity, and substrate type.

PACKAGING AND STORAGE

- Carton of 24 units.
- Shelf life of 1 year.

METHOD OF APPLICATION

SUBSTRATES:

- Interior walls and ceilings.

PREPARATION OF SUBSTRATE:

- The supports, preparatory work, and conditions of application will be in accordance with the DTU and current standards.

APPLICATION TIPS:

- The singular joints connecting walls/ceilings and walls/walls or between 2 walls of different materials must also be treated.
- A thin layer of coating is applied at the joint.
- The fiberglass joint tape is laid in the coating and papered.

CHARACTERISTICS

- Dimensions: 5 cm x 90 m

HEALTH AND SAFETY

The safety data sheet is available on the website: <https://icp-alltek.com/en-gb/documentation/>

RECOMMENDATIONS:

- Ventilate the room during application and drying.
- Use clean and properly maintained PPE: gloves and eye protection designed against liquid splashes, mask during sanding operations.
- To clean tools, scrape off excess and immerse in a minimum amount of water.
- Do not dispose of residues in the sewer. Dispose of contents/container at a hazardous or special waste collection center.
- Store protected from frost and heat.
- Ensure adequate ventilation to remove excess humidity and speed up drying.