

DESCRIPTION

Super lightweight ready-mix plaster for filling and smoothing. No shrinkage, no sanding required. Exceptional ease of use and excellent adhesion. No shrinkage / Low shrinkage (310 ml cartridge).



USE

- Ideal as a paint finish for putty work.
- For a refined finish, sanding may be necessary.
- On painted interior and exterior joinery (except cartridge).
- For outdoor use, Alltek UL must be covered.

TECHNICAL SPECIFICATIONS

TYPICAL SPREADABILITY:

1 litre/m² per mm thickness.

DENSITY:

0,5+/-0,1 kg/l

SOLID CONTENT:

- Solid content by weight: 63%
- Solid content by volume: 85%

APPLICATION CONDITIONS:

- +8°C to +35°C
- Maximum humidity 70% RH

PH:

8 ± 1

CLEANING TOOLS:

With water

RECOMMENDED THICKNESSES:

- Minimum thickness: 0.1 mm
- Maximum thickness: 15 mm

DRYING:

- Approximately 2 hours for a 1 mm application thickness.

PACKAGING AND STORAGE

- 310 ml cartridge (ref. 102839).
- 1-liter jar (ref. 101013).
- 4-liter plastic bucket (ref. 101011).
- Shelf life of 1 year in unopened original packaging, protected from frost and excessive heat.

METHOD OF APPLICATION

SUBSTRATES:

- Plaster, plaster tiles, plasterboards, cement coating, old backgrounds, old paints, printed wood, interior and exterior painted carpentry.
- On powdery substrates, apply a fixative.

ENVIRONMENTAL INFORMATION

- VOC content: < 1 g/L.
- Indoor Air Emission Class



CHARACTERISTICS

- Classification: family III class 2 and family IV class 4b according to AFNOR standard NF T 36-005.
- Product compliant with standard NF EN 16566.

PREPARATION OF SUBSTRATE:

- The supports, preparatory work, and conditions of application will be in accordance with the DTU and current standards.

APPLICATION TIPS:

- Spatula.
- Cartridge pistol.
- Work the product with the spreader knives before use.
- If necessary, add a little water and then knead.
- If necessary, sanding with grain P150 to P220.

RECOMMENDATIONS:

- Ventilate the room during application and drying.
- Use clean and properly maintained PPE: gloves and eye protection designed against liquid splashes, mask during sanding operations.
- To clean tools, scrape off excess and immerse in a minimum amount of water.
- Do not dispose of residues in the sewer. Dispose of contents/container at a hazardous or special waste collection center.
- Conserver à l'abri du gel et de la chaleur.
- Tightly reseal the container after use.
- Ensure adequate ventilation to remove excess humidity and speed up drying.

HEALTH AND SAFETY

The safety data sheet is available on the website: <https://icp-alltek.com/en-gb/documentation/>